



MODEL AAS485MS2

Specifications:

Processor

- AMD® Athlon® 64/64FX/64X2 (Socket AM2), 2GHT/s FSB

Chip Set

- ATI® Radeon Xpress 1150 + SB600

BIOS

- Phoenix (Award) PnP Flash ROM BIOS

Memory

- Four DDR Sockets Supports up to 4GB (Dual Channel DDRII 533/667)

Expansion Slot

- One PCI-E x1 Slot
- Two PCI Slots

Graphic Interface

- One PCI-E x16 Slot

Distributed by:

NETRAID SDN BHD (674948-U)

www.netraid.com.my

Graphics onboard (X300 DirectX 9.0 core)

- Integrated 128-bit 3D/2D Graphics Engines with DirectX 9.0 hardware support.
- Hardware Motion Compensation and iDCT & Hardware MPEG2 Decode (DVD).
- 16MB GDDR for Local Frame Buffer (optional).
- Integrated 24-bit 350MHz RAMDAC.
- Integrated TV Encoder, Macrovision Support, Composite and S-Video Out (Via Cable Adapter), Pal & NTSC Support.

Audio

- Integrated AC97 Controller with Standard AC97 Codec

LAN

- Onboard 10/100/Mb/s or Gigabit Lan

USB 2.0

- Integrated in chipset, USB2.0 x 8

IEEE 1394

- Optional Two IEEE 1394 Firewire Ports

IDE & Serial ATA

- Integrated ATA133 and Serial ATA Controller

Storage & IO Connector

- One Channels Parallel ATA133 Connector (Support up to 2 Devices)
- Four Serial ATA Ports
- One FDD Port (Support 1.44/2.88 MB FDD)
- One Audio Port (Line-in, Line-out, MIC-in)
- One PS/2 Mouse Port
- One PS/2 Keyboard Port
- One Parallel Port
- One Serial Port
- Four USB Ports on Back Panel, four USB on Header with Optional Cable
- One RJ45 Port (10/100 or Gigabit)

HW Monitoring

- CPU & System Overheat Protection

Software

- PC-cillin® Anti Virus

Board Size

- 244mm x 244mm, Micro ATX Form Factor

Distributed by:

NETRAID SDN BHD (674948-U)

www.netraid.com.my